


BHFA-Series Free Flow Strainer

BHFA-Series strainer allows unrestricted air flow service, and prevents unwanted objects from entering the port.

Supplied with standard male pipe thread, unit should be mounted in a protective position, free from excessive vibration. Use wrench on the hex head to tighten unit to the device.



SYMBOL



HOW TO ORDER

BHFA — —

Free Flow Strainer **Connection** **Port Option**
 18 = 1/8" None = NPT
 28 = 1/4" P = BSPT
 38 = 3/8"
 48 = 1/2"



California Proposition 65 Warning

WARNING: This product can expose you to chemicals, including lead, which is known to the state of California to cause Cancer, Birth Defects or other reproductive harm. For more information go to www.p65warnings.ca.gov

SPECIFICATIONS

ITEM	MODEL	BHFA-18	BHFA-28	BHFA-38	BHFA-48
CONNECTION	NPTM	1/8"-27	1/4"-18	3/8"-18	1/2"-14
OVERALL LENGTH	IN. (mm)	0.50" (12.7)	0.70" (17.8)	0.85" (21.7)	0.98" (24.8)
HEX	IN. (mm)	7/16" (11.1)	9/16" (14.2)	11/16" (17.3)	7/8" (22.0)
MATERIAL	BODY	ZINC-PLATED IRON (ZN-Fe)			
	STRAINER	ZINC-PLATED IRON (ZN-Fe)			
MAX OPERATING PRESSURE		300 PSI (21.10 kg/cm ²)			
OPERATING TEMPERATURE		35°~300°F (16°~149°C)			
WEIGHT (APPROX.)	OZ.	0.18	0.37	0.64	1.07
UNIT PACK	EA.	10	10	10	5